



Inferno Outdoor

Sound Barrier

Inferno Outdoor can function as a Sound Barrier or as a traditional siren. Inferno Outdoor effectively stops intruders in their tracks by generating a patented unbearable pattern, frequency and intensity noise. Sound Barrier mode is achieved by pairs or arrays of units. In siren mode, a single Inferno Outdoor covers areas up to 70 square meters/ 750 square feet or direct protection up to 5 meters/ 16 feet. Larger areas can be covered with several units.



- **Generates an unbearable sound**
- **Works with all makes and types of alarm systems**
- **Award winning design - fits easily into public areas and private homes**
- **Sabotage protected with battery backup**

Installation of the Inferno Outdoor cheats the intruder of the few minutes that could be used between alarm activation and arrival of security or police, protecting the secured areas for that crucial period of time and continuing for the duration of continuous signal.

As a Sound Barrier, Inferno Outdoor causes a person to immediately modify their behavior, typically observed as autonomic protective impetus to place ones hands on their ears followed by body motion to immediately remove oneself from the intensity zone.

It is as a behavior modifying Sound Barrier that the value of the patented frequency pattern is achieved. It can be applied to quell, repel or control aggressive, malicious and riot behaviors. This aspect has been applied for protecting Russian nuclear weapons, stores, offices, and distribution plants.

As a siren, Inferno Outdoor is unmistakably loud with a unique intolerable attention getting frequency pattern that clearly stands out from background noise.

Inferno Outdoor has built-in sabotage protection and a battery. The outer casing is made of aluminium and steel which makes it sturdy and durable.

Inferno Outdoor is easily retrofitted to significantly upgrade the effectiveness of existing security system.

Protective volume	Directional or to protect a volume up to 150 cubic meters/5250 cubic feet
Dimensions	L = 685 mm/26.97 in W = 106 mm/4.17 in D = 40 mm/1.58 in
Weight	1.7 kg/ 3.7 lb
Frequency range	2 - 5 kHz
Acoustic effect	125 -127 ±1 dB(A) @ 1 m/3.28 ft, user selectable
Battery backup	9.6 V, 1800 mAh, Ni-MH
Battery lifetime	3 years
Power consumption	12 - 16 V DC, < 150 mA
Function time at cont. signal	> 30 minutes
Standby without charge	Up to 1 month
IP Class	IP 54
Temperature range	-10 — +60 (C), 14 — 140 (F)

Indusec AB

Kampementsgatan 30
SE-115 38 Stockholm, Sweden
Tel: +46 8 4461830, Fax: +46 8 4461831
E-mail: info@inferno.se

Dr. Maurice Goldman
Managing Director US
Tel: 631 235 9500
E-mail: maurice@inferno.se

www.inferno.se